



Acousstop Assort Panel Installation & Care Guide

1-Product Snapshot



Elegant & aesthetic modular panels designed for noise control.



Reduces reverberation and echo; improves speech intelligibility.



High Density Exterior Grade MDF with black acoustical fleece.



Moisture resistant, fire retardant, anti-fungal, low formaldehyde.



Impact resistant with up to 12% open area.



Multiple shades; custom sizes and shapes available.

2. Storage & Handling



Before You Start

- Keep panels flat on a clean, dry, level surface.
- Use protective layering (foam sheets or fabric) between panels to avoid scratches.
- Protect from moisture.



Avoid Compression

- Don't stack too high (Max 800mm) to prevent compression or damage.
- Store in a dry, temperature-controlled area.
- No leaning or bending.

3. Installation

Panels can be installed on walls or ceilings. Ensure the surface is clean, level, and dry before mounting.



Option A – Z-Profile

1. Mark level lines on the wall.
2. Fix Z-Profiles to the wall.
3. Engage each panel onto the Z-Profile.
4. Keep panel gaps consistent.



Option B – Velcro

1. Mark your layout on the wall.
2. Apply industrial Velcro strips to wall and panel.
3. Press panel firmly into place for full adhesion.

Note: Mounting methods depend on the product profile and project instructions. Follow site specifications for fixing hardware and spacing.

4. Care & Cleaning

Regular Maintenance

Clean regularly (twice a month) with a soft brush, microfiber cloth, or vacuum.

Spot Cleaning

Blot gently with a damp cloth. Use mild soap for stubborn stains.

What NOT to use

Avoid abrasive pads, bleach, ammonia, solvents, or high-pressure cleaning.

Environment

Maintain clean HVAC filters and air purifiers. Keep humidity at 65-70%.

5. Do's & Don'ts (Quick Reference)



Do

- Clean panels regularly (twice a month minimum).
- Use only soft brushes or microfiber cloths.
- Maintain indoor humidity at 65-70%.
- Inspect panels periodically for damage.



Don't

- Use abrasive cleaners or harsh chemicals.
- Expose to direct water or excessive humidity.
- Apply high-pressure air or water.
- Ignore dust buildup (reduces performance).

6. Help & Support

India

contactindia@hillpointglobal.com

Dubai

contactdubai@hillpointglobal.com

Qatar

contactqatar@hillpointglobal.com

Saudi Arabia

contactsaudi@hillpointglobal.com