



Acousstop Vibro Roll Installation & Care Guide

1-Product Snapshot



High-density resilient rubber roll designed as a top layer vibration and impact noise control flooring system.



Effectively reduces structure-borne vibration and impact sound transmission.



Bacteria, fungi and water resistance. Anti-slippery resistance.



Impact Insulation Class: 51 dB. Tested as per ASTM E492 and ISO 10140-3.



Durable, non-slip anti-slip textured surface finish. Excellent elastic recovery.



Available in 5 colors: Ocean Blue, Cork, Silver Grey, Lava, Black.

2. Storage & Handling



Before You Start

- Stack rolls on clean, dry, flat surface to prevent deformation.
- Use moisture barrier or plastic sheets for protection.
- Store in temperature-controlled, dry environment.



Avoid Compression

- Do not stack rolls too high; excessive weight may damage the product.
- Store rolls horizontally to avoid bending or warping.
- Do not lean rolls against walls.

3. Installation

Acousstop Vibro Roll is directly fixed over screed, wood or rubber floor. Ensure the surface is clean, level, and dry before installation.



Option A – Dry Lay / Loose Lay Method

1. Clean and level the subfloor surface.
2. Unroll the Vibro Roll across the floor area.
3. Butt edges tightly together without overlapping.
4. Trim to fit using a sharp utility knife.



Option B – Adhesive Fixed Method

1. Clean and prepare the subfloor surface.
2. Apply recommended adhesive to the subfloor.
3. Press the Vibro Roll firmly into place.
4. Allow adhesive to cure fully before use.

Note: Mounting methods depend on the product profile and project instructions. Follow site specifications for fixing hardware and spacing.

4. Care & Cleaning

Regular Maintenance

Clean regularly with a soft brush or vacuum attachment to remove dust and debris.

Spot Cleaning

Blot spills immediately with a damp cloth. Use mild soap and water for stains.

What NOT to use

Avoid abrasive pads, harsh chemicals, or high-pressure cleaning. Do not expose to heavy smoke or chemical spills.

Environment

Keep the area well-ventilated. Avoid dragging heavy sharp objects across the surface to preserve the anti-slip finish.

5. Do's & Don'ts (Quick Reference)



Do

- Clean regularly with soft brush or vacuum.
- Blot spills immediately with a damp cloth.
- Use mild soap and water for stain removal.
- Ensure subfloor is clean, dry and level before installation.



Don't

- Use harsh chemicals or abrasive cleaners.
- Expose to heavy chemical spills or prolonged moisture.
- Drag sharp or heavy objects across the surface.
- Overlap roll edges during installation.

6. Applications & Support

Acousstop Vibro Roll is used in: Yoga Studios, Fitness Centres, Gyms, Music Rooms, Home Theatres, School Class Rooms, Meeting Rooms, and Recording Studios.

India

contactindia@hillpointglobal.com

Dubai

contactdubai@hillpointglobal.com

Qatar

contactqatar@hillpointglobal.com

Saudi Arabia

contactsaudi@hillpointglobal.com